



2PM-33 Series 32Pin Female Angled Cable Plug
Unshielded with Gold-Plated Pin - 2PMΔT33KYH32Г1A1B

Part Number:
2PM33K32WB1

Compatible Part Numbers

Russian P/N	2PMΔT33KYH32Г1A1B
English P/N	2RMDT33KUN32G1A1V
RENHOTEC P/N	2PM33K32WB1

Basic Information

Connector Type	Plug
Orientation	Right Angle
Gender	Female
Shell Size	2PM 33
Number of Positions	32 Pin
Combination No.	5

Mechanical Specification

Contact Termination	Solder
Fastening Type	Threaded
Contact Size	Φ1.5
Durability	500 Cycles

Material Specification

Shell Material	Aluminum Alloy
Contact Material	Brass
Contact Finish	Gold
Insulation Material	Bakelite / Fiberglass / PBT


Electrical Specification

Shielding	Unshielded
Rated Current	10A
Rated Voltage	≤700V (AC)
Insulation Resistance	Normal ≥1000MΩ Moisthea...
Contact Resistance	0.8-5MΩ


Environmental Specification

Operating Temperature	-60℃~+300℃
-----------------------	------------

Contact Layout



Size



Size (mm)					
Shell Size	D1	D2	d	H	L
14	M16×1	22	6.5	40	51
18	M20×1	25	10.5	41	54
22	M24×1	29	14.5	47	59
24	M27×1.5	32	16.5	50	60
27	M30×1.5	35	18.5	53	64
30	M33×1.5	39	20.5	57	65
33	M36×1.5	42	22.5	60	69
36	M39×1.5	45	22.5	63	74
39	M42×1.5	48.5	24.5	66	73
42	M45×1.5	51	30.5	69	76

How to Order

Series:

- 2PM Unsealed
- 2PM-(M Sealed)
- 2PM-(C Sealed bulkhead)

Shell Size:

14.18.22.24.27.30.33.36.39.42.45

Gender:

K(Female) / J(Male)

Contacts:

4.7.8.10.19.20.22.24.30.32.42.45.50

2PM 18 K 4 Q B 2 (5)

Combination No. of contacts: 1.2.3.4.5.6.7.8.9

Plating of contacts:

1 - Gold plated pin 2 - Silver plated pin

Connector type:

- Q: Straight cable plug W: Angled cable plug
- Z: Unsealed socket M: Sealed socket C: Sealed socket bulkhead

Shielded or not of Tail attachment:

A(Shielded) B(Unshielded)

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.