



Push-pull PCB10ZPJ 10 Pin Female Socket with Cover
Solder Cups

Part Number:

PCB10ZPJ



Basic Information

Connector Type	Socket
Orientation	Straight
Gender	Male
Number of Positions	10 Pin
Contact Termination	Solder Cup
Fastening Type	Push-Pull
Mounting Type	Panel Mount
Contact Size	Φ1mm
Color	Golden Yellow/Pale Yellow/Yellow Green

Material Specification

Shell Material	Aluminium Alloy
Shell Finish	Anodizing Treatment
Contact Material	Copper Alloy
Contact Finish	Gold / Silver
Insulation Material	Bakelite


Electrical Specification

Rated Current	3A
Rated Voltage	200V
Contact Resistance	$\leq 8\text{m}\Omega$


Environmental Specification

Operating Temperature	-40°C ~ +105°C
Atmospheric Pressure Range	101.33KPa ~ 6.67Pa
Vibration Resistance	10-2000Hz
IP Rating	IP64

Contact Layout



Size



How to Order

ORDER INFORMATION

Product NO.:

PC-B-4 T K

B: Push-pull connection

Pins: 4,7,10,19, 32, 50 pin

K-Female

J-Male

T-Plug

Z-Receptacle

TP-Plug with cover

ZP-Receptacle+Cover

P-Cover



T
Plug



Z
Receptacle



ZP
Receptacle+Cover



TP
Plug +Cover



P
Cover

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.